



Safety Data Sheet

Revision date: 04/15/2020

Date of issue: 02/20/2018

Version 3.0

Section 1 - Chemical Product and Company Identification

1.1 Product/Chemical Name:

Product Form: Mixture
 Product Name: SLIPS® Dolphin™ Part B
 Product Code: N/A
 Formula: Mixture
 Synonyms: SLIPS® Marine Paint, SLIPS® Bottom Paint, Dolphin Paint
 Chemical Family: Unspecified

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance/mixture Use for creating anti-fouling lubricious surface. For professional use only.

1.3 Details of the supplier of the safety data sheet

Adaptive Surface Technologies,
 85 Bolton St
 Cambridge MA, 02140
 USA
 Phone (617) 360-7080
info@adaptivesurface.tech

1.4 Emergency telephone number

Emergency Number: INFOTRAC – 24/7 Emergency Response for Incidents During Transport
 1-800-535-5053 (Inside U.S.) 1-352-323-3500 (Outside U.S.)

Section 2 - Hazards Identification

2.1 Classification of the substance or mixture

Classification (GHS-US)

Flammable Liquid Category 3 (H226)
 Skin Irritation Category 2 (H315)
 Eye Damage Category 1 (H318)
 Skin Sensitizer Category 1 (H317)
 Germ Cell Mutagen Category 2 (H341)
 Reproductive Toxicity Category 1B (H360)
 Specific Target Organ Toxicity Single Exposure Category 1 (H370)
 Specific Target Organ Toxicity Repeated Exposure Category 1 (H372)
 Aquatic Chronic Toxicity Category 3 (H412)

Full text of H-phrases: see section 16

2.2 Label elements**CLP (EC No. 1272/2008)-GHS-US labeling**

Hazard Pictograms (GHS-US)

Signal word (GHS-US)

Hazard statements (GHS-US)

Danger

H226-Flammable liquid and vapor

H315 - Causes skin irritation

H17-May cause an allergic skin reaction

H318-Causes serious eye damage

H341-Suspected of causing genetic defects

H360-May damage fertility or the unborn child

H370-Causes damage to thymus.

H372 Causes damage to thymus through prolonged or repeated exposure.

H412-Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201-Obtain special instructions before use

P202- Do not handle until all safety precautions have been read and understood

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260-Do not breathe mists, vapors or spray.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling

P270-Do not eat, drink or smoke when using this product

P272-Contaminated work clothing must not be allowed out of the workplace

P273-Avoid release to the environment

P280 - Wear eye protection, protective clothing, protective gloves.

P301+P330+P331- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353-IF ON SKIN(or hair): Remove immediately all contaminated clothing. Rinse skin with shower.

P333+P313-If skin irritation or rash occurs: Get medical attention.

P363 Wash contaminated clothing before reuse

P305+P351+P338+P310- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

P308 + P313 IF exposed or concerned: Get medical advice.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foams, dry chemicals or carbon dioxide to extinguish
P405-Store locked up

P403 + P235 Store in a well-ventilated place. Keep cool

P501- Dispose of contents and container to an approved waste disposal plant

2.3 Other Hazards

The hydrolysis of a component in this mixture is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness).

Section 3 - Composition / Information on Ingredients

3.1 Substance

Not applicable

3.2 Mixture

| Name | Product Identifier | % | Classification (GHS-US) |
|---|---------------------|--------|--|
| Trifluoromethyl C1-4 Alkyl Dimethicone | (CAS No) 63148-56-1 | 47-50% | Not classified |
| Dimethylsiloxane-ethylene oxide block copolymer | 68938-54-5 | 38-40% | Not Classified |
| Silicic acid, tetraethyl ester, hydrolyzed | (CAS No) 68412-37-3 | 10-25% | Eye Irrit 2A, H319 Flam Liq 4, H227 |
| Acetylacetone | (CAS) 123-54-6 | 9% | Flam. Liq. 3, H226 Acute Tox. 4 (oral), H302 Acute Tox. 3 (dermal, inh), H311 + H331 |
| Ethyl silicate | (CAS No) 78-10-4 | <3.5% | Flam Liq 3, H226 Acute Tox inh 4, H332 Eye Irrit 2A, H319 STOT SE 3, H335 |
| Ethanol (hydrolysis product) | (CAS No) 64-17-5 | Varies | Flam Liq 2, H225 Eye Irrit 2A, H319 |
| Dibutyltin dilaurate | (CAS No) 77-58-7 | 3-4% | Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repro 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

| | | | |
|--|--------------------|-----|------------------------------------|
| Allyloxy(polyethylene oxide), methyl ether | (CAS No)27252-80-8 | <3% | Acute Tox 4 (oral), H302 |
| Octamethylcyclotetrasiloxane | (CAS) 556-67-2 | <1% | Flam. Liq 3, H226 Repro 2, H361 |

Full text of H-phrases: see section 16

Section 4 - First Aid Measures

4.1 Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | Remove contaminated clothing and shoes. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). |
| First-aid measures after inhalation | Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists. |
| First-aid measures after skin contact | Rinse immediately with plenty of soap and water. Obtain medical attention if irritation develops or persists. |
| First-aid measures after eye contact | Rinse cautiously with water for at least 20 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Obtain immediate medical attention. |
| First-aid measures after ingestion | Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor. |

4.1 Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------|--|
| Symptoms/injuries | Causes severe eye irritation. Eye damage is possible. |
| Symptoms/injuries after inhalation | May cause respiratory irritation. |
| Symptoms/injuries after skin contact | May cause skin irritation. |
| Symptoms/injuries after eye contact | Causes serious eye damage. Symptoms may include: redness, pain, swelling, itching, burning, tearing, and blurred vision. |
| Symptoms/injuries after ingestion | Ingestion may cause gastrointestinal irritation and other adverse effects. |
| Chronic symptoms | Exposure may cause damage to the thymus. Contains a chemical that may adversely affect reproduction and is suspected to cause genetic effects. |

4.3. Indication of any immediate medical attention and special treatment needed

Immediate medical attention is recommended for eye contact. If medical advice is needed, have product container or label at hand.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | Use water spray, alcohol-resistant foams, dry chemicals or carbon dioxide |
| Unsuitable extinguishing media | Do not use a heavy water stream. Application of water stream to hot product may cause frothing and increase fire intensity. |

5.2 Special hazards arising from the substance or mixture

| | |
|--------------|--|
| Fire hazard: | Flammable liquid and vapor. Vapors will collect in low and confined areas and may travel along surfaces to remote ignition sources and flash back. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame. |
| Reactivity: | Hazardous reactions will not occur under normal conditions |

5.3 Advice for firefighters

| | |
|--------------------------------|--|
| Precautionary measures fire | Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present. |
| Firefighting instructions | Use water spray or fog for cooling exposed containers. Do not allow run-off from firefighting to enter drains or water courses. |
| Protection during firefighting | Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus for firefighting if necessary. |
| Other information | Refer to Section 9 for flammability properties |

Section 6 - Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

| | |
|------------------|--|
| General measures | Remove ignition sources. Use special care to avoid static electric charges. Avoid all contact with skin, eyes, or clothing. Use special care. Do not breathe vapor, mist or spray. For personal protection, see section 8. |
|------------------|--|

6.1.1 For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | Use appropriate personal protection equipment (PPE). |
| Emergency procedures | Evacuate personnel to safe areas. |

6.1.2 For emergency responders

| | |
|----------------------|---|
| Protective equipment | Equip cleanup crew with proper protection. |
| Emergency procedures | Stop leak if safe to do so. Ventilate area. |

6.2 Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| For containment | Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Keep in suitable, closed containers for disposal. |
| Methods for cleaning up | Absorb and/or contain spill with inert material, then place in suitable container. Clear up spills immediately and dispose of waste safely. Use only non-sparking tools. |

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.



Section 7 - Handling and Storage

7.1. Precautions for safe handling

Additional hazards when processed Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Hygiene measures Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Ground and bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage conditions Store in a dry, cool and well-ventilated place. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store away from heat.

Incompatible products Strong acids, strong bases, strong oxidizers, moist air, water, store away from heat.

7.3. Specific end use(s)

Use for creating anti-fouling lubricious surface. For professional use only.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | Value | Control Parameters | Basis |
|------------------------------|---------|-------|------------------------|---------------|
| Ethyl silicate | 78-10-4 | IDLH | 700 ppm | USA IDLH |
| | | TWA | 85 mg/m ³ | USA NIOSH REL |
| | | TWA | 10 ppm | USA NIOSH REL |
| | | TWA | 850 mg/m ³ | USA OSHA PEL |
| | | TWA | 100 ppm | USA OSHA PEL |
| Ethanol (hydrolysis product) | 64-17-5 | IDLH | 3300 ppm (10%LEL) | USA IDLH |
| | | TWA | 1900 mg/m ³ | USA NIOSH REL |
| | | TWA | 1000 ppm | USA NIOSH REL |
| | | TWA | 1900 mg/m ³ | USA OSHA PEL |
| | | TWA | 1000 ppm | USA OSHA PEL |

Safety Data Sheet

According to 29CFR1910.1200-2012 and EC No. 1907/2006 (REACH) (as amended)

| | | | | |
|-------------------------------------|----------|------|-----------------------|---|
| Acetylacetone (2,4-pentanedione) | 123-54-6 | TWA | 25 ppm skin | USA ACGIH TLV |
| Dibutyltin dilaurate | 77-58-7 | TWA | 0.1 mg/m ³ | USA OSHA- Table Z-1 Limits for Air contaminants |
| | | TWA | 0.1 mg/m ³ | USA ACGIH TLV |
| | | STEL | 0.2 mg/m ³ | USA ACGIH TLV |
| | | TWA | 0.1 mg/m ³ | USA NIOSH REL |
| | | TWA | 0.1 mg/m ³ | USA OSHA- Table Z-1 Limits for Air contaminants |
| | | TWA | 0.1 mg/m ³ | USA ACGIH TLV |
| | | STEL | 0.2 mg/m ³ | USA ACGIH TLV |
| | | TWA | 0.1 mg/m ³ | USA NIOSH REL |
| | | PEL | 0.1 mg/m ³ | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| | | STEL | 0.2 mg/m ³ | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| | | | | |

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

Hand protection

Wear protective gloves. Inspect before each use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash & dry hands after use. Recommended neoprene or nitrile for glove material for short term exposure (≤30min).

Eye protection

Tightly fitting chemical goggles or safety glasses. Use equipment for eye protection tests and approved under appropriate government standards such as NIOSH (US).

| | |
|---|--|
| Skin and body protection | Wear suitable protective clothing. Wash contaminated clothing before reuse. |
| Respiratory protection | Use a NIOSH-approved organic vapor (black cartridge) respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits. |
| Section 9 - Physical and Chemical Properties | |
| 9.1. Information on basic physical and chemical properties | |
| Physical state | Liquid |
| Appearance | clear, light yellow tint |
| Odor | Mild |
| Odor threshold | No data available |
| pH | No data available |
| Evaporation Rate | No data available |
| Melting point | No data available |
| Freezing point | No data available |
| Boiling point | >= 136°C (277°F) |
| Flash point | 38°C (100°F) |
| Auto-ignition Temperature | No data available) |
| Decomposition temperature | No data available |
| Flammability (solid, gas) | Flammable liquid and vapor |
| Vapor pressure | No data available |
| Relative vapor density at 20 °C | No data available |
| Relative density | No data available |
| Specific Gravity | No data available |
| Solubility | Insoluble with water. Reacts with water. |
| Partition coefficient: n-octanol/water | No data available |
| Viscosity | 50-100 cP |
| 9.2 Other information | |
| VOC content | < 10 % |
| Section 10 - Stability and Reactivity | |
| 10.1 Reactivity | |
| Hazardous reactions will not occur under normal conditions. | |
| 10.2 Chemical stability | |
| Stable at standard temperature and pressure. | |
| 10.3 Possibility of hazardous reactions | |
| Some materials in this mixture decomposes slowly when in contact with moist air or water, generating ethanol. | |
| 10.4 Conditions to avoid | |

Direct sunlight. Extremely high or low temperatures. Incompatible materials. Heat. Open flames. Sparks.

10.5 Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6 Hazardous decomposition products

Ethanol. Organic acid vapors. Silicon dioxide. Silicon oxides. Carbon oxides (CO, CO₂). Tin/tin oxides.

Section 11- Toxicological Information

11.1 Information on toxicological effects

Acute toxicity Not classified

| Ethyl polysilicate (68412-37-3) | |
|--|----------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rat | > 4450 mg/kg |
| Ethyl silicate (78-10-4) | |
| LD50 oral rat | 6270 mg/kg |
| LDLo inhalation rat | 1000 ppm/4h |
| Ethanol (64-17-5) | |
| LC50 inhalation rat (mg/l) | 124.7 mg/l/4h |
| Dibutyltin dilaurate (77-58-7) | |
| LD50 oral rat | 2071 mg/kg |
| LD50 dermal rat | > 2000 mg/kg |
| Allyloxy(polyethylene oxide), methyl ether (27252-80-8) | |
| LD50 oral rat | >500 mg/kg |
| Acetylacetone (123-54-6) | |
| LD50 oral rat | 570-560 mg/kg |
| LD50 dermal rabbit | 790-1370 mg/kg |
| LC50 inhalation rat | 5.1 mg/L/4 h |

Skin corrosion/irritation Classified as a skin irritant.

| Dibutyltin dilaurate (77-58-7) | |
|---------------------------------------|---|
| Skin- Rabbit | Category 1C-where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days |

Serious eye damage/irritation Causes severe eye irritation. Eye damage is possible.

Respiratory or skin sensitization May cause skin sensitization.

Germ cell mutagenicity Suspected of causing genetic defects.

| Dibutyltin dilaurate (77-58-7) | |
|---|--|
| In vitro tests showed mutagenic effects | Not mutagenic in Ames Test. Positive results were obtained in some in vitro tests. |

Carcinogenicity Not classified

Reproductive toxicity May damage fertility or the unborn child.

Contains Octamethylcyclotetrasiloxane which

is suspected of damaging fertility based on animal data.

Dibutyltin dilaurate (77-58-7)

Presumed human reproductive toxicant

Developmental toxicity-rat-oral:
Specific developmental abnormalities:
Craniofacial (including nose and tongue),
musculoskeletal system

Specific target organ toxicity (single exposure)

Classified

Dibutyltin dilaurate (77-58-7)

Causes damage to organs

Target organ-Thymus

Specific target organ toxicity (repeated exposure)

Classified

Dibutyltin dilaurate (77-58-7)

Causes damage to organs through prolonged or repeated exposure

Target organ-Thymus

Aspiration hazard

Not classified

Symptoms/injuries after inhalation

May cause respiratory irritation.

Symptoms/injuries after skin contact

May cause skin irritation.

Symptoms/injuries after eye contact

Causes serious eye damage. Symptoms may include:
redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/injuries after ingestion

Ingestion may cause gastrointestinal irritation and other adverse effects.

Chronic symptoms

Exposure may cause damage to the thymus. Contains a chemical that may adversely affect reproduction and is suspected to cause genetic effects.

Section 12 - Ecological Information**12.1 Toxicity****Ethyl polysilicate (68412-37-3)**

EC50 Daphnia 1

>193 mg/l (Exposure time: 48 h- Species
Daphnia magna)

Ethanol (64-17-5)

LC50 fish 1

12.0-16.0 ml/l(exposure time: 96 h- Species:
Oncorhynchus mykiss [static])

EC50 Daphnia 1

9268-14221 mg/l (Exposure time: 48h- Species:
Daphnia magna)

LC50 fish 2

>100mg/l (Exposure time: 96 h- Species:
Pimephales promelas [static])

EC50 Daphnia 2

2mg/l (Exposure time: 48 h- Species: Daphnia
magna [static])

Dibutyltin dilaurate (77-58-7)

EC50 Daphnia

<0.46 mg/l (Exposure time: 48 h- Species:
Daphnia magna)

Acetylacetone (123-54-6)

| | |
|--------------|---|
| EC50 Daphnia | 40 mg/l (Exposure time: 48 h- Species: Daphnia magna) |
| LC50 fish | 106 mg/L/96 hr |

No additional information available

12.2 Persistence and degradability

No additional information available

12.3 Bioaccumulative potential

| Ethanol (64-17-5) | |
|-------------------|-------|
| Log Pow | -0.32 |

12.4 Mobility in soil

No additional information available

12.5 Other adverse effects

Other information Avoid release to the environment. Harmful to aquatic life with long lasting effects.

Section 13 – Disposal considerations



13.1 Waste treatment methods

Waste disposal recommendations Incinerate. Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology-waste materials Avoid release to the environment



Section 14 – Transport information

In accordance with DOT / IMDG / IATA

| | 14.1 UN Number | 14.2 UN Proper Shipping Name | 14.3 Transport Hazard Class(es) | 14.4 Packing Group | 14.5 Environmental Hazards | Additional info |
|----------|----------------|------------------------------|--|--------------------|--|--|
| DOT (US) | UN1263 | PAINT | 3. Flammable liquids   | III | Yes Marine Pollutant (dibutyltin dilaurate) | The environmentally hazardous substance mark is not required when transported in sizes of <5 L or <5kg and on non-bulk packages unless transported by vessel |

Safety Data Sheet

According to 29CFR1910.1200-2012 and EC No. 1907/2006 (REACH) (as amended)

| | | | | | | |
|------|--------|-------|---|-----|-----|--|
| IMDG | UN1263 | PAINT | 3. Flammable liquids  | III | Yes | |
| IATA | UN1263 | PAINT | 3. Flammable liquids  | III | Yes | |

Transport by sea

No additional information available

Air transport

No additional information available

Section 15 – Regulatory information

15.1 US Federal regulations

US Federal regulations

TSCA: All components of this formulation are listed in the TSCA Inventory (40 CFR710). This product is subject to export notification.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 HAZARD CLASSIFICATION: Refer to Section 2 for the OSHA Hazard Classification.

EPA SARA 313: This product contains the following chemicals that are regulated under SARA Title III, section 313:
None

US State regulations

This product is not known to contain chemicals regulated under California Proposition 65.

| Dibutyltin dilaurate (77-58-7) | |
|---------------------------------------|-----------------------------|
| Pennsylvania Right to Know Components | Revision Date 1993-02-16 |
| New Jersey Right to Know Components | Revision Date 1993-02-16 |
| | |
| Acetylacetone (123-54-6) | |

| | |
|--|---|
| Pennsylvania Right to Know Components | Revision Date 1993-02-16 |
| New Jersey Right to Know Components | Revision Date 1993-02-16 |
| EU Regulations: This product is classified and labeled in accordance with EC CLP. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006 (REACH) | |
| Section 16 – Other information | |
| Revision date | 04/15/2020 |
| Other information | This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200. |
| Full text of H-phrases | |
| Acute Tox inh | Acute inhalation toxicity |
| Aquatic Acute | Acute Aquatic toxicity |
| Aquatic Chronic | Chronic Aquatic toxicity |
| Eye Dam. | Serious eye damage |
| Eye Irrit | Eye Irritation |
| Flam Liq | Flammable liquid |
| Muta | Germ Cell Mutagen |
| Repro | Reproductive Toxicity |
| Skin Corr | Skin Corrosion |
| Skin Sens | Skin Sensitization |
| STOT SE | Specific Target Organ Toxicity Single Exposure |
| STOT RE | Specific Target Organ Toxicity Repeated Exposure |
| H226 | Flammable liquid and vapor |
| H227 | Combustible Liquid |
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |
| H335 | Nay cause respiratory irritation |
| H341 | Suspected of causing genetic defects |
| H360 | May damage fertility or the unborn child |
| H361 | Suspected of damaging fertility or the unborn child. |
| H370 | Causes damage to organs |
| H372 | Causes damage to organs through prolonged or repeated exposure |

Safety Data Sheet

According to 29CFR1910.1200-2012 and EC No. 1907/2006 (REACH) (as amended)

| | |
|------|--|
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

Acute Tox. 3 (dermal, inh), H311 + H331

| | |
|--------------------|---|
| NFPA health hazard | 3 |
| NFPA fire hazard | 2 |
| NFPA instability | 0 |

We believe that the information contained herein is current as of the date of this Safety Data Sheet and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of Adaptive Surface Technologies, it is the user's obligation to determine the conditions of safe use of the product.